

CERTIFIKAT

Solar Keymark Certificate No. SP SC0054-14

Holder/Issued to

Company:

Westech Solar Technology Wuxi Co., Ltd

Address:

No.28 ChangKang Road, Wuhaoqiao Industrial Park, Mashan, Wuxi, Jiangsu,

China 214091

Product name and description

Vacuum tube thermal solar collector. For technical information see Appendix.

Model:

WT-TF-2

Certificate

The product mentioned above is found to comply with requirements in EN 12975-1:2006+A1:2010 and EN 12975-2: 2006 and the Specific CEN Keymark Scheme Rules for Solar Thermal Products.

Marking

Products conforming to this certificate shall be marked in accordance with the requirements in the Specific CEN Keymark Scheme Rules for Solar Thermal Products. The marking shall, together with the Keymark logo, show the identification code of the empowered certification body (SP Technical Research Institute of Sweden, No. 012), also see CEN-CENELEC Internal Regulations Part 4 Certification, Annex A.

Validity

This certificate is valid until 2019-01-15 provided that the conditions in the Solar Keymark Rules are fulfilled and the standard or rules are not modified significantly. The validity of the certificate can be checked in the database, see Solar Keymark website http://www.solarkeymark.org

Miscellaneous

The manufacturer's factory production control procedures are under surveillance by the responsibility of SP. This is the first version of this certificate.

Borås, Sweden 2014-01-15

SP Technical Research Institute of Sweden

Certification

ennart Aronsson

Product Certification Manager

Susanne Hansson Certification Officer





Annex to Solar Keymark Certificate

Page 1/2

est Results,					Certifica	ite num	ber	SP	SC0054	-14	
annex to Solar KEYMARK Certificate						issue	2014-01-15				
Westech Sc	olar Techn	ology Wux	d Co., Ltd	Co., Ltd Country China							
·								vestechs	estechsolar com		
	Road No.	28							******************	*************	
****	rioda)iio		***************************************			***********************	000000000000000000000000000000000000000		***********************		
		***************************************	***************************************			***************************************					
	/ 1	-11						dannament menter men			
	/ un-glazed	a)			Evacuated	tubular	collector				
ble?					No					MARKASAN MARKASAN	
						Po	wer outp	ut per c	ollector u	ınit	
	ure Aa)				AG)		G =	1000 W	//m²		
	erti	oss	oss	oss	oss ea (Tm-Ta:			
	Ap	G G	N G	Gr	4	0 K	10 K	30 K	50 K	70 K	
	[m²]	[mm]	[mm]	[mm]	[m²]	[W]	[W]	[W]	[W]	[W]	
	1.57	1982	1010	110	2.00	918	901	863	819	770	

***************************************	ļ			***************************************	ļ		ļ				
***************************************	ļ									***************************************	
***************************************	ļ					ļ	1		-	***************************************	
***************************************										***************************************	
						 	<u> </u>				
						<u> </u>				*************	
		 					·····			***************************************	
			••••••	***************************************						•••••	

					фоноворов по	-		\$	·		
						η _{0a}		0.59	 -		
ers related to <u>a</u>	perture are	ea (Aa)				η0a a _{1a}		0.59 1.03	- W/(m²K))	
ers related to <u>a</u> e note 1	perture are	ea (Aa)				}		1.03	- W/(m²K) W/(m²K²	*************	
e note 1						a _{1a} a _{2a}		1.03 0.005	W/(m²K²	***************	
_						a _{1a} a _{2a} tstg	A.	1.03 0.005 285.5	W/(m²K²	²)	
e note 1						a _{1a} a_{2a} $tstg$ $Ceff = C/a$	Aa	1.03 0.005 285.5 7.31	W/(m ² K ² °C kJ/(m ² K)	²)	
e note 1	ns see note	2 2				a _{1a} a _{2a} tstg Ceff = C/		1.03 0.005 285.5 7.31 600	W/(m ² K ² °C kJ/(m ² K) kPa	2)	
e note 1 ather condition e note 3	ns see note G _{DIF} /	: 2 / _{G_{TOT}}	θ _τ / θ _L	50°	10°	a_{1a} a_{2a}	30°	1.03 0.005 285.5 7.31 600 40°	W/(m²K² °C kJ/(m²K) kPa 60°	²) 70°	
e note 1	ns see note G _{DIF} / min	/G _{TOT}	$K_{\theta}(\theta_{T})$			a _{1a}		1.03 0.005 285.5 7.31 600	W/(m ² K ² °C kJ/(m ² K) kPa	70°	
e note 1 ather condition e note 3	ns see note G _{DIF} /	: 2 / _{G_{TOT}}				a_{1a} a_{2a}	30°	1.03 0.005 285.5 7.31 600 40° 1.02	W/(m²K² °C kJ/(m²K) kPa 60°	²) 70°	
e note 1 ather condition e note 3	ns see note G _{DIF} / min	/G _{TOT}	$K_{\theta}(\theta_{T})$	 0.86		a _{1a} a _{2a} tstg Ceff = C/ pmax 20° 0.98	30° Optional	1.03 0.005 285.5 7.31 600 40° 1.02 values	W/(m²K² °C kJ/(m²K) kPa 60° 1.09	70°	
e note 1 ather condition e note 3	ns see note G _{DIF} / min	/G _{TOT}	$K_{\theta}(\theta_{T})$	 0.86		a_{1a} a_{2a} a	30° Optional	1.03 0.005 285.5 7.31 600 40° 1.02 values	W/(m²K² °C kJ/(m²K) kPa 60° 1.09	70°	
e note 1 ather condition e note 3	ns see note G _{DIF} / min	/G _{TOT}	$K_{\theta}(\theta_{T})$	 0.86		a_{1a} a_{2a} $tstg$ $ceff = C/A$ $pmax$ 0.98 $rices Shell$ $www.in$	30° Optional nzhen Ltc	1.03 0.005 285.5 7.31 600 40° 1.02 	W/(m²K² °C kJ/(m²K) kPa 60° 1.09	70°	
e note 1 ather condition e note 3	ns see note G _{DIF} / min	/G _{TOT}	$K_{\theta}(\theta_{T})$	 0.86		a _{1a}	30° Optional nzhen Ltd tertek.co	1.03 0.005 285.5 7.31 600 40° 1.02 	W/(m²K² °C kJ/(m²K) kPa 60° 1.09	70°	
e note 1 ather condition e note 3	ns see note G _{DIF} / min	/G _{TOT}	$K_{\theta}(\theta_{T})$	 0.86		a _{1a}	30° Optional nzhen Ltc tertek.co 052GZU-0	1.03 0.005 285.5 7.31 600 40° 1.02 	W/(m²K² °C kJ/(m²K) kPa 60° 1.09	70°	
e note 1 ather condition e note 3 0)	ns see note G _{DIF} / min	/G _{TOT}	$K_{\theta}(\theta_{T})$	 0.86		a _{1a}	30° Optional nzhen Ltd tertek.co	1.03 0.005 285.5 7.31 600 40° 1.02 	W/(m²K² °C kJ/(m²K) kPa 60° 1.09	70°	
e note 1 ather condition e note 3	ns see note G _{DIF} / min	/G _{TOT}	$K_{\theta}(\theta_{T})$	 0.86		a _{1a}	30° Optional nzhen Ltc tertek.co 052GZU-0	1.03 0.005 285.5 7.31 600 40° 1.02 	W/(m²K² °C kJ/(m²K) kPa 60° 1.09	70°	
e note 1 ather condition e note 3 0)	ns see note G _{DIF} / min	/G _{TOT}	$K_{\theta}(\theta_{T})$	 0.86		a _{1a}	30° Optional nzhen Ltc tertek.co 052GZU-0	1.03 0.005 285.5 7.31 600 40° 1.02 	W/(m²K² °C kJ/(m²K) kPa 60° 1.09	70°	
e note 1 ather condition e note 3 0)	ns see note G _{DIF} / min	/G _{TOT}	$K_{\theta}(\theta_{L})$ $K_{\theta}(\theta_{L})$	 0.86	esting Serv	a _{1a}	30° Optional nzhen Ltd tertek.co 052GZU-(1-02 75-2 6.1.	1.03 0.005 285.5 7.31 600 40° 1.02 	W/(m²K² °C kJ/(m²K) kPa 60° 1.09 zhou Bran	70°	
e note 1 ather condition e note 3 0) uring pry:	G _{DIF} /min 0.13	/G _{TOT} max 0.18	$K_{\theta}(\theta_{T})$ $K_{\theta}(\theta_{L})$	 0.86 Intertek T	esting Serv	a _{1a}	30° Optional nzhen Ltd tertek.co 052GZU-(1-02 75-2 6.1.	1.03 0.005 285.5 7.31 600 40° 1.02 	W/(m²K² °C kJ/(m²K) kPa 60° 1.09 zhou Bran	70°	
e note 1 ather condition e note 3 0) uring pry:	G _{DIF} /min 0.13	/G _{TOT} max 0.18	$K_{\theta}(\theta_{T})$ $K_{\theta}(\theta_{L})$	 0.86 Intertek T	esting Serv	a _{1a}	30° Optional nzhen Ltd tertek.co 052GZU-(1-02 75-2 6.1.	1.03 0.005 285.5 7.31 600 40° 1.02 	W/(m²K² °C kJ/(m²K) kPa 60° 1.09 zhou Bran	70°	
֡֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜	Westech Sc Westech Changkang 214091 Wuxi	Westech Solar Techn Westech Changkang Road,No. 214091 Wuxi acuate tubular / un-glazed ple ? (Pg) (pg) [m²]	Westech Solar Technology Wux Westech Changkang Road,No.28 214091 Wuxi acuate tubular / un-glazed) ole ? March	Westech Solar Technology Wuxi Co., Ltd Westech Changkang Road,No.28 214091 Wuxi acuate tubular / un-glazed) ole ? [m²] [mm] [mm]	Westech Solar Technology Wuxi Co., Ltd Westech Changkang Road,No.28 214091 Wuxi acuate tubular / un-glazed) ole ? Main	Westech Solar Technology Wuxi Co., Ltd Westech Changkang Road,No.28 214091 Wuxi Fax acuate tubular / un-glazed) Die? Water	Westech Solar Technology Wuxi Co., Ltd Westech Changkang Road, No.28 E-mail 214091 Tel. Wuxi Fax acuate tubular / un-glazed) Die? No Po [m²] [mm] [mm] [mm] [m²] [W]	Westech Solar Technology Wuxi Co., Ltd Westech Changkang Road,No.28 E-mail Sales@ 214091 Tel. +86 Wuxi Fax +86 acuate tubular / un-glazed) Evacuated tubular collector of G = No Power outgray G = O K 10 K [m²] [mm] [mm] [mm] [m²] [W] [W]	Westech Solar Technology Wuxi Co., Ltd Country China Westech Website www.westechs Sales@westech Sales@westech	Westech Solar Technology Wuxi Co., Ltd Country China	

4P00211 OBL fr SC0976-13



Annex to Solar Keymark Certificate

Page 2/2

Annual collector output based on EN 12975 Test Results,	Certificate number	SP SC0054-14
annex to Solar KEYMARK Certificate	Date of issue	2014-01-15

Annual collector output kWh															
	Location and collector temperature (Tm)														
Collector name		Athen	5	Davos			Stockholm			Würzburg			T		
	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C			
WT-TF-2	1466	1283	1090	1249	1070	895	901	753	615	966	808	657			
		•													
				***************************************									-		
**************************************	·····		***************************************				***************************************		***************************************	***************************************					
		***************************************	######################################				***************************************	•••••	***************************************					ļ	
									***************	***************************************		***************************************			
	†		•••••											<u> </u>	

Collector mounting: Fixed or tracking Fixed; slope = latitude - 15° (rounded to nearest 5°)

Overview of locations								
Location	Latitude °	Gtot kWh/m²	Ta °C	Collector orientation or tracking mode				
Athens	38	1 765	18.5	South, 25°				
Davos	47	1 714	3.2	South, 30°				
Stockholm	59	1 166	7.5	South, 45°				
Würzburg	50	1 244	9.0	South, 35°				

Gtot	Annual total irradiation on collector plane	kWh/m²
Та	Mean annual ambient air temperature	°C
Tm	Constant collector operating temperature (mean of in- and outlet temperatures)	°C

Calculation of the annual collector performance is done by the official Solar Keymark spreadsheet tool. Hour by hour the collector output is calculated according to the efficiency parameters from the Keymark test using constant collector operating temperature (Tm). Detailed description with all equations used is available from the Solar Keymark web site (direct link: http://www.estif.org/solarkeymark/annexb1.php)

SP Technical Research Institute of Sweden Box 857, 501 15 Borås, Sweden

4P00211 OBL fr SC0976-13

VERSION 3.6, 2012.01.20

Calculation program version:

4.05, Nov, 2013 (SP)